


PRODUCTS AND
TECHNOLOGIES
FOR PAINT STRIPPING


WITH AN ATTENTIVE
EYE TO NATURE



WWW.CONDOROIL.IT



CONDOROILCHEMICAL
THE SUPPORTABLE CHEMICAL FOR INDUSTRY



PRODUCTS AND TECHNOLOGIES FOR PAINT STRIPPING

CARBON STEEL POWDER PAINTS



PAINT STRIPPER SVA 581 - SVA 582

MATERIAL TO PAINT STRIP:
KIND OF PAINT TO REMOVE:
APPLICATION :
WORKING PRINCIPLES:
CHARACTERISTICS:

WORKING TEMPERATURE:

STEEL AND STAINLESS STEEL .
POWDER, ED-PAINT
CONCENTRATION AS DELIVERED - TEMPERATURE 60-70°C
IT DISSOLVES PAINT
FREE OF HARMFUL SUBSTANCES BY INHALATION, FREE OF
CHLORINATED SOLVENTS, AMMINES AND PHENOLS
SVA 581 70-80°C
SVA 582 40-50°C

CARBON STEEL ED-PAINT



PAINT STRIPPER SVI 590

MATERIAL TO PAINT STRIP:
KIND OF PAINT TO REMOVE:
APPLICATION :
WORKING PRINCIPLES:
CHARACTERISTICS

STEEL AND STAINLESS STEEL
POWDER, LIQUID, ED-PAINT
CONCENTRATION AS DELIVERED - TEMPERATURE 60 °C
IT DISSOLVES PAINT
FREE OF HARMFUL SUBSTANCES BY INHALATION - IT CLEAN
RECESS SPOTS, FREE OF CHLORINATED SOLVENTS AND PHENOLS

ALUMINIUM AND ZAMAK



PAINT STRIPPER SVI 520

MATERIAL TO PAINT STRIP:
KIND OF PAINT TO REMOVE:
APPLICATION :
WORKING PRINCIPLES:
CHARACTERISTICS

STEEL, DIE-CASTING, MAGNESIUM, ALUMINIUM AND ZAMAK
POWDER, ED-PAINT
CONCENTRATION AS DELIVERED - TEMPERATURE 50-60°C
IT DISSOLVES PAINT
FREE OF HARMFUL SUBSTANCES BY INHALATION - IT REMOVES
CHROMATIZING, IT CLEANS RECESS SPOTS
FREE OF CHLORINATED SOLVENTS, AMMINES, PHENOLS AND
PYRROLIDONE

ALUMINIUM AT AMBIENT TEMPERATURE



PAINT STRIPPER SVI 565 SVI 568 - PAINT STRIPPER SVA 583



MATERIAL TO PAINT STRIP:
KIND OF PAINT TO REMOVE:
APPLICATION :
WORKING PRINCIPLES:
CHARACTERISTICS

ALL METALS AND SOME PLASTICS
POWDER, ED-PAINT
CONCENTRATION AS DELIVERED - AMBIENT TEMPERATURE
IT DISSOLVES PAINT
FREE OF HARMFUL SUBSTANCES BY INHALATION - IT CLEANS
RECESS SPOTS AND PRESERVE CHROMATIZING
FREE OF CHLORINATED SOLVENTS, AMMINES AND PHENOLS
SVI 568 IS FREE OF PYRROLIDONE TOO
SVA 583 IS FREE OF HAZARD IDENTIFICATION: "HARMFULL FOR THE
HEALTH" GHS-08 "

TOUGH PAINTS



PAINT STRIPPER SVI 506 and SVI 506 PH

MATERIAL TO PAINT STRIP:
KIND OF PAINT TO REMOVE:
APPLICATION :
WORKING PRINCIPLES:
CHARACTERISTICS:

ALL METALS
ANY PAINTS
CONCENTRATION AS DELIVERED - ROOM TEMPERATURE
IT SWELLS AND REMOVES THE PAINT
THEY ARE METHYLENE CHLORIDE AND PHENOLS BASED

CONDOROIL CHEMICAL, FOCUSED ON SURFACE TREATMENT FOR MORE THAN 40 YEARS, PROPOSE A SERIES OF INNOVATIVE AND HIGH PERFORMING PRODUCTS FOR PAINT STRIPPING.
HERE ARE A SELECTION OF THE MAIN PRODUCTS AND EQUIPMENT

WOOD PRODUCTS



PAINT STRIPPER SVA 584



MATERIAL TO PAINT STRIP:
KIND OF PAINT TO REMOVE:
APPLICATION :
WORKING PRINCIPLES:
CHARACTERISTICS

WOOD
LIQUID
CONCENTRATION AS DELIVERED - TEMPERATURE 35-50°C
IT DISSOLVES PAINT
FREE OF METHYLENE CHLORIDE AND FORMIC ACID

SPECIAL TRANSPARENT PAINTS



PAINT STRIPPER SVI 510

MATERIAL TO PAINT STRIP:
KIND OF PAINT TO REMOVE:
APPLICATION :
WORKING PRINCIPLES:
CHARACTERISTICS

STEEL, STAINLESS STEEL, MAGNESIUM, ALUMINIUM AND ZAMAK ALLOYS
LIQUID, POWDER
CONCENTRATION AS DELIVERED - TEMPERATURE 60 °C
IT DISSOLVES PAINT
FREE OF HARMFUL SUBSTANCES BY INHALATION - IT CLEAN RECESS SPOTS, FREE OF CHLORINATED SOLVENTS AND PHENOLS

PAINT STRIPPING UNITS



PAINT STRIPPING UNITS

PAINT STRIPPING UNIT COMPLE OF:

- TANK IN CARBON OR STAINLESS STEEL MATERIAL
 - AGITATION AND HEATING SYSTEMS
 - OPTIONS LIKE THERMAL INSULATION, WORKPIED HOLDER BASKETS, DESLUDGING UNIT, DRAINING BAGS, ETC.
- NOTE: THE UNIT CAN BE PROVIDED WITH BARREL FOR HEAVY LOAD OF SMALL ITEMS

PAINT STRIPPING SPRAY UNIT

PAINT STRIPPING SPRAY UNIT FOR THE TREATMENT OF HEAVY LOAD OF HOOKS AND RACKS.
IN THE SAME STATION THE ITEM ARE ALSO RINSED WITH UNDER PRESSURE WATER JET.

IN LINE PAINT STRIPPING UNIT



IN LINE PAINT STRIPPING UNIT

BEST OPTION FOR THE TREATMENT OF THE HOOKS AND RACKS HAVING THE SAME SHAPE.

THE UNIT, ACCORDING TO THE DIMENSIONS OF THE ITEM TO BE CLEANED, CAN WORK WITH SPRAY OR ULTRASONIC TECHNOLOGY.



CONDOROILCHEMICAL

THE SUPPORTABLE CHEMICAL FOR INDUSTRY

www.CONDOROIL.IT

CONDOROIL CHEMICAL
VIA GALLIANI, 50-60-62
21020 CASALE LITTA VA ITALY
T. +39 0332 945212
info@condoroil.it

02.16